



(19)

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 505 929 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
04.06.1997 Bulletin 1997/23

(51) Int Cl.⁶: **G01N 27/447**

(21) Application number: **92104816.1**

(22) Date of filing: **19.03.1992**

(54) Two-dimensional electrophoresis apparatus

Vorrichtung für zweidimensionale Elektrophorese

Appareil électrophorèse à deux dimensions

(84) Designated Contracting States:
DE FR GB

(30) Priority: **29.03.1991 JP 93710/91**

(43) Date of publication of application:
30.09.1992 Bulletin 1992/40

(73) Proprietor: **SHIMADZU CORPORATION**
Nakagyo-ku Kyoto-shi Kyoto 604 (JP)

(72) Inventor: **Nakanura, Shin**
Sakyo-ku, Kyoto 606 (JP)

(74) Representative: **Goddard, Heinz J., Dr.**
FORRESTER & BOEHMERT
Franz-Joseph-Strasse 38
80801 München (DE)

(56) References cited:
EP-A- 0 393 478 **DE-A- 3 816 626**
DE-A- 3 939 850

EP 0 505 929 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to an electrophoresis apparatus, and more particularly, it relates to a two-dimensional electrophoresis apparatus for making a two-dimensional electrophoresis with an one-dimensional gel housing which stores an one-dimensional gel and an two-dimensional gel housing which stores a two-dimensional gel.

Description of the Background Art

In general, a two-dimensional electrophoresis method is carried out in the following procedure: First, an one-dimensional gel is formed in a glass tube, to make an one-dimensional electrophoresis in relation to a sample such as protein with the one-dimensional gel. Then, the one-dimensional gel, in which the sample is separated and fractionated through the one-dimensional electrophoresis, is connected to a two-dimensional slab gel which is previously formed between two glass plates, to make a two-dimensional electrophoresis while transferring the sample fractions of the two-dimensional gel.

In a conventional two-dimensional electrophoresis method, such electrophoresis steps are manually carried out by an operator. For example EP 0 393 478 turns to the problem of transferring a gel cylinder and discloses a composite product which comprises a cylindrically shaped gel and a multifilament thread extending through the length of said gel to provide projecting ends of said thread extending from opposite ends of said cylinder. However, it nevertheless takes great skill to handle the gels, while the respective operations are complicated. Therefore, it is difficult to improve reproducibility of separated images and separative power.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a two-dimensional electrophoresis apparatus which can improve reproducibility of separated images and separative power by enabling automatic implementation of a two-dimensional electrophoresis.

The two-dimensional electrophoresis apparatus according to the present invention comprises a gel transfer means which comprises a grasping mechanism for grasping said one-dimensional gel housing,

a moving mechanism for raising up the lower end of said one-dimensional gel housing to a position higher than the upper end of said two-dimensional gel housing and horizontally moving said one-dimensional gel housing longitudinally along the up-

per end of said two-dimensional gel, and an extrusion mechanism for extruding said one-dimensional gel from said one-dimensional gel housing at the same speed as said horizontal movement of said one-dimensional gel housing induced by said moving mechanism.

Since the gel transfer means according to the invention automatically transfers the first-dimensional gel from the first-dimensional gel housing to the end of the second-dimensional gel housing, reproducibility of separated images and separative power are improved with no regard to the skill of an operator.

The foregoing and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a front elevational view showing a two-dimensional electrophoresis apparatus according to an embodiment of the present invention;

Fig. 2 is a perspective view schematically showing the internal mechanism of the electrophoresis apparatus;

Fig. 3 is a perspective view showing a principal part of the internal mechanism;

Fig. 4 is a partially fragmented longitudinal sectional view showing a transcription part of the electrophoresis apparatus;

Fig. 5 is a schematic block diagram showing a control part of the electrophoresis apparatus;

Fig. 6 is a control flow chart thereof;

Fig. 7 is a control flow chart thereof;

Fig. 8 is a perspective view corresponding to Fig. 3, showing a state of the apparatus in its operation;

Fig. 9 is a perspective view corresponding to Fig. 3, showing another state of the apparatus in its operation; and

Fig. 10 is a perspective view corresponding to Fig. 3, showing still another state of the apparatus in its operation.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Fig. 1 shows a two-dimensional electrophoresis apparatus 1 according to an embodiment of the present invention. This two-dimensional electrophoresis apparatus 1 has an apparatus body 2, a control panel 3 which is arranged on the front surface of the apparatus body 2, and a front door 4 which is arranged under the control panel 3. The front door 4 is openable, so that an operator can approach a mechanism which is arranged in the apparatus body 2.

Fig. 2 shows the mechanism which is arranged in the apparatus body 2. Referring to Fig. 2, an one-dimen-

sional electrophoresis part 5 and a two-dimensional electrophoresis part 6 are arranged on this side of the apparatus 1. A transcription part 7 is arranged above these electrophoresis parts 5 and 6. Further, an X-axis driving part 8 for driving the transcription part 7 in an X-axis direction (horizontal direction) and a Z-axis driving part 9 for driving the transcription part 7 in a Z-axis direction (vertical direction) are arranged on the other side of the apparatus 1. The transcription part 7, the X-axis driving part 8 and the Z-axis driving part 9 form gel transfer means.

The X-axis driving part 8 comprises a feed screw 10 extending in the X-axis direction and a stepping motor 11 for rotating and driving the feed screw 10. The feed screw 10 is fitted with a female screw part (not shown), which is provided on a base 12 of the Z-axis driving part 9. The Z-axis driving part 9 has a feed screw 13 upwardly projecting from the base 12 and a stepping motor 14 for rotating and driving the feed screw 13. The feed screw 13 is fitted with a female screw part (not shown), which is provided on the transcription part 7.

As shown in Fig. 3, the one-dimensional electrophoresis part 5 has a housing 20 which is formed by a glass tube for storing an one-dimensional gel, a holder 21 holding the upper end of the housing 20, an upper reservoir 22 which is fixed to the holder 21, and a lower reservoir 23 receiving the lower end of the housing 20. The central portion of the housing 20 is enclosed with a temperature control block 24 which is controlled by a Peltier element. The upper and lower reservoirs 22 and 23 are provided with upper and lower electrodes 25 and 26 respectively.

The two-dimensional electrophoresis part 6 has a housing 30 which is formed by a pair of glass plates holding a planarly spread slab gel, an upper reservoir 31 which is provided on the upper portion of the housing 30, a lower reservoir 32 receiving the lower portion of the housing 30, and a clamp 33 enclosing the central portion of the housing 30. The clamp 33 is provided with a temperature control block 34, which is temperature-controlled by a Peltier element. The upper and lower reservoirs 31 and 32 are provided with upper and lower electrodes 35 and 36 respectively. The upper reservoir 31 is further provided with a supply nozzle 37 for supplying an electrode liquid to the upper reservoir 31.

Fig. 4 shows a structure which is provided in a frame 40 of the transcription part 7. Referring to Fig. 4, the transcription part 7 is provided on its lower portion with a chuck 41 for grasping the upper reservoir 22 (Fig. 3). This chuck 41 is opened/closed by a stepping motor 43 through a cam mechanism 42. Further, a vertically extending gel extrusion rod 44 is arranged in the frame 40. An upper end of this rod 44 is fixed to a holding plate 45, which is slidable with respect to a vertically extending guide shaft 46 and tapped for being adapted for screwing to a vertically extending feed screw 47. The feed screw 47 is rotated and driven by a stepping motor 48 which is arranged on the upper portion of the frame

40, thereby vertically moving the holding plate 45. The lower portion of the rod 44 is inserted in a centering cylindrical member 49 which is provided on the lower end portion of the frame 40. The centering cylindrical member 49 is adapted to engage with the upper end portion of the housing 20 in operation of this apparatus 1, to align center lines of the housing 20 and the gel extrusion rod 44 with each other.

The frame 40 is further provided with a downwardly projecting discharge nozzle 50 on its lower portion. This discharge nozzle 50 is coupled to a suction mechanism (not shown) through a tube 51.

Fig. 5 schematically shows a control part 60 of the two-dimensional electrophoresis apparatus 1. The control part 60 includes a microcomputer which is formed by a CPU, a ROM, a RAM and the like. The control part 60 is connected with various keys 61 which are arranged on the control panel 3 (Fig. 1), a display part 62 of an LCD, and a buzzer 63 for generating a warning sound. The control part 60 is also connected with the X-axis driving part 8 and the Z-axis driving part 9 shown in Fig. 2, a chuck driving part 64 including the motor 43 shown in Fig. 4, and a rod driving part 65 including the motor 48. The control part 60 is further connected with a primary electrode liquid discharge part 66 including a suction pump for discharging a primary electrode liquid through the discharge nozzle 50 (Fig. 4) etc., a secondary electrode liquid supply part 67 including a supply pump for supplying a secondary electrode liquid from the supply nozzle 37 to the upper reservoir 31 etc., a primary voltage applying part 68 for applying a voltage across the electrodes 25 and 26 of the one-dimensional electrophoresis part 5, and a secondary voltage applying part 69 for applying a voltage across the electrodes 35 and 36 of the two-dimensional electrophoresis part 6. The control part 60 is further connected with other input/output parts such as control parts for the temperature control blocks 24 and 34.

The operation of the two-dimensional electrophoresis apparatus 1 is now described with reference to flow charts shown in Figs. 6 and 7.

When the program is started, initialization is made at a step S1 of Fig. 6 to arrange the transcription part 7 above the one-dimensional electrophoresis part 5 etc., and the process is advanced to a step S2. At the step S2, the operator operates the keys 61 of the control panel 3, to select an operation mode. For example, a desired electrophoresis mode is selected from modes of managing the electrophoresis state with time, with the product of voltage and time, with the product of current and time, and with the product of power and time, and the process is advanced to a step S3.

At the step S3, various processing conditions such as the processing time for the electrophoresis, the applied voltage and the like are inputted through the control panel 3. Then the process is advanced to a step S4, to wait for the operator pressing a start key.

The operator opens the front door 4, to set the hous-

ing 20, storing a gel which contains a sample, in the one-dimensional electrophoresis part 5, and introduces electrode liquids into the reservoirs 22 and 23. The operator further sets the housing 30 storing a slab gel in the two-dimensional electrophoresis part 6, introduces an electrode liquid only into the lower reservoir 32, and stores an equilibrium liquid in the upper end portion of the housing 30. When prescribed adjustment which is required for starting the electrophoresis is completed, the operator inputs a start command through the control panel 3. Upon receiving the start command, the process is advanced from the step S4 to a step S5.

At the step S5, an one-dimensional electrophoresis is executed on the basis of the processing mode and the processing conditions set at the steps S2 and S3. After the one-dimensional electrophoresis is completed, the process is advanced to a step S6. At the step S6, the transcription part 7 is downwardly moved to insert the discharge nozzle 50 into the upper reservoir 22 of the first-dimensional electrophoresis part 5, as shown in Fig. 8. At a step S7, the electrode liquid is discharged from the upper reservoir 22 through the discharge nozzle 50. Then the process is advanced to a step S8, to temporarily move up the transcription part 7.

At a step S9, the chuck 41 is opened. At a step S10, the transcription part 7 is downwardly moved toward the one-dimensional electrophoresis part 5. At this time, the transcription part 7 is so downwardly moved that the centering cylindrical member 49 engages with the upper end portion of the housing 20 in the upper reservoir 22. When the cylindrical member 49 engages with the upper end portion of the housing 20, the gel extrusion rod 44 is rendered concentric with the housing 20.

At a step S11, the chuck 41 is closed to grasp the upper reservoir 22. At a step S12, the transcription part 7 is upwardly moved to move up the upper reservoir 22 with the chuck 41, so that the housing 20 is upwardly extracted from the temperature control block 24. When the housing 20 is completely extracted, the transcription part 7 is moved to a position above the two-dimensional electrophoresis part 6 at a step S13, as shown in Fig. 9.

Then the process is advanced to a step S14, to start downward movement of the gel extrusion rod 44. Thus, the rod 44 is inserted in the housing 20, to start downward extrusion of the gel from the housing 20. At a step S15, the transcription part 7 is moved in the X-axis direction along the housing 30. The distance of movement of the transcription part 7 along the X-axis direction coincides with the length of the gel extruded by the gel extrusion rod 44. Consequently, the gel completing the one-dimensional electrophoresis is arranged on the upper end portion of the housing 30.

A step S16 is adapted to wait for completion of the gel extrusion started at the step S14 and the movement of the transcription part 7 in the X-axis direction started at the step S15. If a determination of yes is made at the step S16, the process is advanced to a step S17 shown in Fig. 7. At this time, the gel extruded from the housing

20 is dipped in the equilibrium liquid which is stored in the upper end portion of the housing 30. Fig. 10 shows an operation state attained when a determination of yes is made at the step S16.

At the step S17, the transcription part 7 is moved back to its initial position. At a step S18, the gel extrusion rod 44 is upwardly moved and extracted from the housing 20.

A step S19 is adapted to wait for completion of gel equilibrium with the equilibrium liquid on the housing 30 of the two-dimensional electrophoresis part 6. When a determination is made on completion of such equilibrium, the process is advanced to a step S20. At the step S20, the supply nozzle 37 supplies an electrode liquid into the upper reservoir 31. At a step S21, a prescribed voltage is applied across the electrodes 35 and 36, thereby executing a second-dimensional electrophoresis.

When the two-dimensional electrophoresis is completed, the process is advanced to a step S22 to sound the buzzer 63 and display completion of the processing on the display part 62. Then the process is returned to the step S2 shown in Fig. 6.

According to this embodiment, as hereinabove described, the transcription part 7 transfers the first-dimensional gel from the one-dimensional electrophoresis part 5 to the two-dimensional electrophoresis part 6 so that the two-dimensional electrophoresis is automatically executed, whereby it is possible to save labor as well as to improve reproducibility of separated images and separative power with no regard to skillfulness of the operator.

When no equilibrium is carried out, the operator may previously introduce an electrode liquid into the upper reservoir 31 of the two-dimensional electrophoresis part 6 in setting. In this case, it is possible to omit the supply nozzle 37 and the structure related thereto.

The temperature control blocks 24 and 34 comprising Peltier elements may be omitted and the lower reservoirs 23 and 32 may be increased in size to dip the housings 20 and 30 in the electrode liquids which are contained in the reservoirs 23 and 32, thereby controlling temperatures thereof. In this case, a temperature control part is used for adjusting the temperatures by circulating the electrode liquids contained in the lower reservoirs 23 and 32.

The two-dimensional electrophoresis apparatus according to the present invention comprises the gel transfer means for transferring the one-dimensional gel completely electrophoresed by the one-dimensional electrophoresis means from the one-dimensional gel housing to an end of the two-dimensional gel housing. According to the present invention, therefore, it is possible to automatically transfer the one-dimensional gel, thereby improving reproducibility of separated images and separative power with no regard to skillfulness of an operator.

Although the present invention has been described

and illustrated in detail, it is clearly understood that the same is by way of illustration and example only and is not to be taken by way of limitation, the invention being limited by the terms of the appended claims.

Claims

1. A two-dimensional electrophoresis apparatus for making a two-dimensional electrophoresis using a one-dimensional gel housing storing a one-dimensional gel and a two-dimensional gel housing storing a two-dimensional gel, said two-dimensional electrophoresis apparatus comprising:

one-dimensional electrophoresis means for making a one-dimensional electrophoresis of said one-dimensional gel;
two-dimensional electrophoresis means for making a two-dimensional electrophoresis of said two-dimensional gel; and
gel transfer means for transferring said one-dimensional gel, being completely electrophoresed by said one-dimensional electrophoresis means, from said one-dimensional gel housing to one end of said two-dimensional gel housing,

characterized in that
said gel transfer means comprises:

a grasping mechanism for grasping said one-dimensional gel housing,
a moving mechanism for raising up the lower end of said one-dimensional gel housing to a position higher than the upper end of said two-dimensional gel housing and horizontally moving said one-dimensional gel housing longitudinally along the upper end of said two-dimensional gel, and
an extrusion mechanism for extruding said one-dimensional gel from said one-dimensional gel housing at the same speed as said horizontal movement of said one-dimensional gel housing induced by said moving mechanism.

2. A two-dimensional electrophoresis apparatus in accordance with claim 1, wherein
the upper end portion of said one-dimensional gel housing is fixed to a upper reservoir containing an electrode liquid, and said grasping mechanism of said gel transfer means grasps said one-dimensional gel housing through said upper reservoir.
3. A two-dimensional electrophoresis apparatus in accordance with claim 1, wherein said extrusion mechanism comprises:

a vertically movable gel extrusion rod,
a vertical mechanism for vertically moving said rod, and
a centering member slidably supporting said rod for aligning center lines of said rod and said one-dimensional gel housing when said grasping mechanism grasps said one-dimensional gel housing.

4. A two-dimensional electrophoresis apparatus in accordance with claim 3, wherein

said vertical mechanism comprises:
a tapped holder fixed to the upper end of said rod and supported to be movable along a vertical guide shaft, and
a feed screw extending vertically, being adapted for screwing into said tapped holder, and being driven by a motor for vertically moving said holder.

5. A two-dimensional electrophoresis apparatus in accordance with claim 3, wherein

said one-dimensional gel housing is a cylindrical glass tube, and
said centering member is a cylindrical member whose inner diameter is equal to the outer diameter of said glass tube, so that said rod slides along its center.

6. A two-dimensional electrophoresis apparatus in accordance with claim 2, wherein
said gel transfer means comprises drain means for discharging said electrode liquid from said upper reservoir of said one-dimensional gel housing.

Patentansprüche

1. Vorrichtung für eine zweidimensionale Elektrophorese zum Durchführen einer zweidimensionalen Elektrophorese unter Verwendung eines Gehäuses für ein eindimensionales Gel, das ein eindimensionales Gel aufnimmt, und eines Gehäuses für ein zweidimensionales Gel, das ein zweidimensionales Gel aufnimmt, wobei die Vorrichtung für eine zweidimensionale Elektrophorese umfaßt:

eine Einrichtung für eine eindimensionale Elektrophorese zum Durchführen einer eindimensionalen Elektrophorese des eindimensionalen Gels;
eine Einrichtung für eine zweidimensionale Elektrophorese zum Durchführen einer zweidimensionalen Elektrophorese des zweidimensionalen Gels; und eine Gelüberführeinrichtung zum Überführen des eindimensionalen

- Gels, das von der Einrichtung für eine eindimensionale Elektrophorese vollständig elektrophoresiert ist, von dem Gehäuse für ein eindimensionales Gel zu einer Seite des Gehäuses für ein zweidimensionales Gel, dadurch gekennzeichnet, daß
- die Gelüberföhreinrichtung umfaßt:
- einen Greifmechanismus zum Greifen des Gehäuses für ein eindimensionales Gel,
- einen Schiebermechanismus zum Anheben der unteren Seite des Gehäuses für ein eindimensionales Gel zu einer Position, die höher als die obere Seite des Gehäuses für ein zweidimensionales Gel ist, und horizontalen Bewegungen des Gehäuses für ein eindimensionales Gel in Längsrichtung entlang der oberen Seite des zweidimensionalen Gels, und
- einen Extrusionsmechanismus zum Extrudieren des eindimensionalen Gels aus dem Gehäuse für ein eindimensionales Gel mit derselben Geschwindigkeit wie die von dem Schiebermechanismus eingeleitete horizontale Bewegung des Gehäuses für ein eindimensionales Gel.
2. Vorrichtung für eine zweidimensionale Elektrophorese nach Anspruch 1, dadurch gekennzeichnet, daß der oberseitige Abschnitt des Gehäuses für ein eindimensionales Gel an einem oberen Behälter befestigt ist, der eine Elektrodenflüssigkeit enthält, und der Greifmechanismus der Gelüberföhreinrichtung das Gehäuse für ein eindimensionales Gel über den oberen Behälter greift.
3. Vorrichtung für eine zweidimensionale Elektrophorese nach Anspruch 1, dadurch gekennzeichnet, daß der Extrusionsmechanismus umfaßt:
- eine vertikal bewegbare Geextrusionsstange, einen vertikalen Mechanismus zum vertikalen Bewegen der Stange, und
- ein die Stange gleitfähig haltendes Zentrierelement zum Ausrichten der Mittellinien der Stange und des Gehäuses für ein eindimensionales Gel, wenn der Greifmechanismus das Gehäuse für ein eindimensionales Gel greift.
4. Vorrichtung für eine zweidimensionale Elektrophorese nach Anspruch 3, dadurch gekennzeichnet, daß der vertikale Mechanismus umfaßt:
- einen mit einem Innengewinde versehenen Halter, der an dem oberen Ende der Stange befestigt ist und gehalten wird, um entlang einer vertikalen Führungsschse bewegbar zu sein, und eine sich vertikal erstreckende Vorschubspindel, die in den mit einem Innengewinde versehenen Halter schraubbar ist und von einem Motor zum vertikalen Bewegen des Halters angetrieben wird.

5. Vorrichtung für eine zweidimensionale Elektrophorese nach Anspruch 3, dadurch gekennzeichnet, daß das Gehäuse für ein eindimensionales Gel ein zylindrisches Glasrohr ist und das Zentrierelement ein zylindrisches Element ist, dessen Innendurchmesser gleich dem Außendurchmesser des Glasrohres ist, so daß die Stange entlang seiner Mitte gleitet.
6. Vorrichtung für eine zweidimensionale Elektrophorese nach Anspruch 2, dadurch gekennzeichnet, daß die Gelüberföhreinrichtung eine Ablaufeinrichtung zum Ablassen der Elektrodenflüssigkeit aus dem oberen Behälter des Gehäuses für ein eindimensionales Gel umfaßt.

Revendications

1. Appareil d'électrophorèse bidimensionnelle pour l'exécution d'une électrophorèse bidimensionnelle au moyen d'une boîte à gel unidimensionnel emmagasinant un gel unidimensionnel et d'une boîte à gel bidimensionnel emmagasinant un gel bidimensionnel, cet appareil d'électrophorèse bidimensionnelle comprenant :
- un moyen d'électrophorèse unidimensionnelle pour l'exécution d'une électrophorèse unidimensionnelle du gel unidimensionnel, un moyen d'électrophorèse bidimensionnelle pour l'exécution d'une électrophorèse bidimensionnelle du gel bidimensionnel, et un moyen de transfert de gel pour le transfert du gel unidimensionnel complètement électrophorésé par le moyen d'électrophorèse unidimensionnelle de la boîte à gel unidimensionnel à une extrémité de la boîte à gel bidimensionnel, caractérisé par le fait que le moyen de transfert de gel comprend :
- un mécanisme de saisie de la boîte à gel unidimensionnel,
- un mécanisme de mouvement pour faire monter l'extrémité inférieure de la boîte à gel unidimensionnel à une position plus haute que l'extrémité supérieure de la boîte à gel bidimensionnel et déplacer horizontalement la boîte à gel unidimensionnel longitudinalement le long de l'extrémité supérieure de la boîte à gel bidimensionnel, et
- un mécanisme d'extrusion pour extruder le gel unidimensionnel de la boîte à gel unidimensionnel à la vitesse du mouvement horizontal de la boîte à gel unidimensionnel produit par le mécanisme de mouvement.
2. Appareil d'électrophorèse bidimensionnelle selon la revendication 1, dans lequel la partie d'extrémité supérieure de la boîte à gel uni-

dimensionnel est fixée à un réservoir supérieur contenant un liquide électrode, et le mécanisme de saisie du moyen de transfert de gel saisit la boîte à gel unidimensionnel à travers ce réservoir supérieur.

5

3. Appareil d'électrophorèse bidimensionnelle selon la revendication 1, dans lequel le mécanisme d'extrusion comprend :

une tige d'extrusion de gel mobile verticalement, 10

un mécanisme vertical pour mouvoir verticalement cette tige, et

un élément de centrage supportant en coulissement cette tige pour aligner les axes de cette tige et de la boîte à gel unidimensionnel lorsque le mécanisme de saisie saisit la boîte à gel unidimensionnel. 15

4. Appareil d'électrophorèse bidimensionnelle selon la revendication 3, dans lequel le mécanisme vertical comprend :

un support taraudé fixé à l'extrémité supérieure de la tige et supporté pour être mobile le long d'un arbre vertical de guidage, et 25

une vis d'avance s'étendant verticalement, faite pour se visser dans le support taraudé et entraînée par un moteur pour mouvoir verticalement le support. 30

5. Appareil d'électrophorèse bidimensionnelle selon la revendication 3, dans lequel

la boîte à gel unidimensionnel est un tube cylindrique en verre, et 35


l'élément de centrage est un élément cylindrique dont le diamètre intérieur est égal au diamètre extérieur du tube en verre, de sorte que la tige coulisse le long de son axe. 40

6. Appareil d'électrophorèse bidimensionnelle selon la revendication 2, dans lequel le moyen de transfert de gel comprend un moyen d'écoulement pour la décharge du liquide électrode du réservoir supérieur de la boîte à gel unidimensionnel. 45

50

55

FIG.1






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG .7




FIG. 8




FIG. 9




FIG.10

